# DS-2CE17D0T-IT5F(C)
## 2 MP Camera





- High quality imaging with 2 MP, 1920 × 1080 resolution
- 3.6 mm, 6 mm, 8 mm, 12 mm fixed focal lens
- Up to 80 m IR distance for bright night imaging
- One port for four switchable signals (TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP67)

## ▪ Specification


| | |
|---|---|
| **Camera** | |
| Image Sensor | 2 MP CMOS |
| Signal System | PAL/NTSC |
| Frame Rate | TVI: 1080P@30fps, 1080P@25fps<br>CVI: 1080P@30fps, 1080P@25fps<br>AHD: 1080P@30fps, 1080P@25fps<br>CVBS: PAL/NTSC |
| Resolution | 1920 (H) × 1080 (V) |
| Min. illumination | 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR |
| Shutter Time | PAL: 1/25 s to 1/50,000 s<br>NTSC: 1/30 s to 1/50,000 s |
| Lens | 3.6 mm, 6 mm, 8 mm, 12 mm fixed lens |
| Horizontal Field of View | 3.6 mm, horizontal FOV: 79.6°, vertical FOV: 43.5°, diagonal FOV: 93.7°<br>6 mm, horizontal FOV: 51.9°, vertical FOV: 30°, diagonal FOV: 58.8°<br>8 mm, horizontal FOV: 39.9°, vertical FOV: 21.9°, diagonal FOV: 46.5°<br>12 mm, horizontal FOV: 24.6°, vertical FOV: 13.9°, diagonal FOV: 28.1° |
| Lens Mount | M12 |
| Day & Night | ICR |
| WDR (Wide Dynamic Range) | Digital WDR |
| Angle Adjustment | Pan: 0 to 360°, Tilt: 0 to 180°, Rotation: 0 to 360° |
| **Menu** | |
| Image Mode | STD/HIGH-SAT |
| AGC | Yes |
| Day/Night Mode | Auto/Color/BW (Black and White) |
| White Balance | Auto/Manual |
| AE (Auto Exposure) Mode | DWDR/BLC/HLC/Global |
| Language | English |
| Functions | Brightness, Sharpness, Smart IR |
| 2D DNR | Yes |
| **Interface** | |
| Video Output | Switchable TVI/AHD/CVI/CVBS |
| **General** | |
| Operating Condition | -40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation) |
| Power Supply | 12 VDC ± 25% |
| Power Consumption | Max. 4.7 W |
| Protection Level | IP67 |
| Material | Front Cover: Metal<br>Main Body: Plastic |
| IR Range | Up to 80 m |
| Communication | HIKVISION-C |
| Dimensions | 78.9 mm × 75.4 mm × 216.6 mm (3.10" × 2.97" × 8.53") |
| Weight | Approx. 320 g (0.71 lb.) |

## ▪ Dimension



## ▪ Accessory





DS-1280ZJ-XS

## ▪ Available Model

DS-2CE17D0T-IT5F(C)

Distributed by


**Headquarters**
No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

**Hikvision USA**
T +1-909-895-0400
sales.usa@hikvision.com

**Hikvision Europe**
T +31-23-5542770
sales.eu@hikvision.com

**Hikvision UK & Ireland**
T +01628-902140
sales.uk@hikvision.com

**Hikvision UAE**
T +971-4-4432090
salesme@hikvision.com

**Hikvision Russia**
T +7-495-669-67-99
saleru@hikvision.com

**Hikvision Australia**
T +61-2-8599-4233
salesau@hikvision.com

**Hikvision Italy**
T +39-0438-6902
info.it@hikvision.com

**Hikvision South Africa**
Tel: +27 (10) 0351172
sale.africa@hikvision.com

**Hikvision Singapore**
T +65-6684-4718
sg@hikvision.com

**Hikvision Korea**
T +82-(0)31-731-8817
sales.korea@hikvision.com

**Hikvision India**
T +91-22-28469900
sales@pramahikvision.com

**Hikvision Brazil**
T +55 11 3318-0050
Latam.support@hikvision.com

**Hikvision France**
T +33(0)1-85-330-450
info.fr@hikvision.com

**Hikvision Spain**
T +34-91-737-16-55
info.es@hikvision.com

**Hikvision Poland**
T +48-22-460-01-50
info.pl@hikvision.com

**Hikvision Canada**
T +1-866-200-6690
sales.canada@hikvision.com

**Hikvision Turkey**
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

**Hikvision Kazakhstan**
T +7-727-9730667
nikia.panfilov@hikvision.ru

**Hikvision Tashkent**
T +99-87-1238-9438
uzb@hikvision.ru

**Hikvision Indonesia**
T +62-21-2933759
Sales.Indonesia@hikvision.com

**Hikvision Thailand**
T +662-275-9949
sales.thailand@hikvision.com

**Hikvision Malaysia**
T +601-7652-2413
sales.my@hikvision.com

**Hikvision Vietnam**
T +84-974270888
sales.vt@hikvision.com

**Hikvision Hong Kong**
T +852-2151-1761
info.hk@hikvision.com

**Hikvision Colombia**
sales.colombia@hikvision.com


© Hikvision Digital Technology Co., Ltd. 2021 | Data subject to change without notice |