
# CABLE UTP CAT 5E (80%COBRE) INTERIOR - 305M - BLANCO

C721

| | |
|---|---|
| Bending Radius (min) | ≥ 8xOD(without load) |
| Pulling Tension (max) | ⩾12.5MP |
| **General Specifications** | |
| Pair Construction | |
| Pair Color Codes | Blue |
| | Orange |
| | Green |
| | Brown |
| **Compliance (International Standards)** | |
| | EIA/TIA 568 & ISO/IEC 11801 |
| **Printing** | |
| | Customerized |
| **Test and results** | |
| Inflamability test | CM |
| Transmission Parameters | |

| | |
|---|---|
| **Construction** | |
| Jacket | PVC-WHITE |
| Conductor | CCA (Copper Clad Aluminum) |
| Cond.size | 4*2*0.5mm |
| Insulator | HDPE |
| Pair construction | Unshielded Twisted |
| **Cable dimensions (AWG - mm)** | |
| Length | 305M(±5M) |
| Weight | 6.5KG |
| Diameter over jacket | 5.2mm |
| Jacket Thickness | 0.65mm |
| | |
| **Electric Specifications** | |
| DC Resistance | ⩽14Ω/100M |
| DC Resistance Unbalance | MAX 2.5% |
| Mutual Capacitance | MAX 5.6NF /100M |
| Capacitance Unbalance | Max 330NF/100M |
| Characteristic Impedance | 100±15Ω |
| Voltage rating (Vrms) | 30V |
| Dielectric Strength | 5000mΩ/km |
| Velocity of Propagation | 0.62C |
| Propagation Delay | 536ns |
| Propagation Delay Skew | 45ns |
| | |
| **Ambiental Specifications** | |
| Installation Temperature | -20℃-50℃ |
| Operating Temperature | -20℃-50℃ |
| **Mechanical Specifications** | |




## DESCRIPCIÓN

- Cable utp categoria 5E - 24 awg 4p*0,5mm (aleacion)
  305 metros outdoor jacket pe color negro - carrete de madera

