dimax

ACCESO RFID INTEGRADO

R316

CARACTERÍSTICAS

Estos dispositivos de la serie son controles de acceso RFID/teclado/huella digital independientes con carcasa de metal y diseño integrado; la entrada y salida wiegand los hace también controladores o lectores wiegand.

- Caja metálica, diseño integrado.
- Resistente al agua, conforme a IP66
- Un relé, autónomo
- Tipo de tarjeta: Tarjeta EM de 125 KHz
- Modo pulso, modo alternante
- LDR incorporado para evitar manipulaciones
- Salida Wiegand de 26 bits
- Identificación automática de entrada Wiegand 26/34 bits



ESPECIFICACIONES

User Capacity	**1000 Cards/PINs**
Normal Users	990
Visitor Users	10
Operating Voltage	**12-18V DC**
Idle Current	30mA
Active Current	120mA
Keypad	**12 Keys**
Proximity Card Reader	**EM**
Radio Technology	125KHz EM Card
Read Range	0-6cm
Wiring Connections	Relay Output, Exit Button,Wiegand (in/out)
Relay	**One (NO, NC, Common)**
Adjustable Relay Output Time	0-99 Seconds (5 seconds default)
Lock Output Load	2Amp Maximum
Environment	**Outdoor**
Operating Temperature	-40℃~60℃, -40℉~140℉
Operating Humidity	10%RH-90%RH
Physical	**Stainless Steel Plate**
Color	Silver & Black
Dimensions	115x70x25mm
Unit Weight	245g
Shipping Weight	285g

