dimax

ACCESO RFID INTEGRADO

R314

CARACTERÍSTICAS

Estos dispositivos de la serie son controles de acceso RFID/teclado/huella digital independientes con carcasa de metal y diseño integrado; la entrada y salida wiegand los hace también controladores o lectores wiegand.

- Caja metálica, diseño integrado.
- Resistente al agua, conforme a IP66
- Un relé, autónomo
- Tipo de tarjeta: Tarjeta EM de 125 KHz
- Modo pulso, modo alternante
- LDR incorporado para evitar manipulaciones
- Salida Wiegand de 26 bits
- Identificación automática de entrada Wiegand 26/34 bits



ESPECIFICACIONES

User Capacity Card	**2000** EM Card
Operating Voltage Idle Current	**12-24V DC** ＜50mA
Proximity Card Reader Radio Technology Read Range	**EM** 125KHz 0-6cm
Wiring Connections	Relay Output, Exit Button, Wiegand (in/out)
Relay Adjustable Relay Output Time Time Lock Output Load	**One (NO, NC, Common)** 0-99 Seconds (5 seconds default) 2 Amp Maximum
Environment Operating Temperature Operating Humidity	**Meets IP66** -40˚C～60˚C (-40°F～140°F) 0%RH～98%RH
Physical Color Dimensions Unit Weight Shipping Weight	**Stainless Steel Plate** Silver & Black 115x70x25mm 230g 270g

