dimax

# KIT DE CERRADURA CON HUELLA DACTILAR IP65

R321

## CARACTERÍSTICAS

- Totalmente inalámbrico, sin necesidad de cables
- Fácil de instalar y operar
- Tiempos de apertura: 16 000 veces para la cerradura, 10 000 veces para el teclado
- Tecnología de código variable de 433 MHz
- Consumo de energía ultrabajo
- Con dos transmisores remotos
- Teclado de huella digital inalámbrico de metal (IP65)
- 1000 usuarios (incluidos 100 usuarios de huella digital + 900 usuarios de PIN/tarjeta)
- PIN de 4 a 6 dígitos, EM de 125 KHz
- Distancia de comunicación: 20 m máx.
- Apertura de la cerradura mediante teclado, botón de salida inalámbrico y transmisores remotos
- Duración de la batería: más de 12 meses



## ESPECIFICACIONES

| | |
|---|---|
| **User Capacity** | 1000 Users (100 fingerprint users + 900 PIN / card users) |
| **PIN Length** | 4-6 digits |
| **Card Type** | 125KHz EM |
| **Operating Voltage** | |
| Wireless Lock / Wireless Keypad | 2 units of AA batteries / 3 units of AAA batteries |
| Wireless Exit Button / Remote Transmitter | 1 unit of 2032 Lithium battery / 1 unit of 2032 Lithium battery |
| **Idle Current** | All items < 10uA |
| **Working Current** | |
| Wireless Keypad/Wireless Lock | < 50mA / < 42mA |
| Wireless Exit Button/Remote Transmitter | < 3mA / < 3mA |
| **Communication Frequency** | 433MHz |
| **Communication Distance** | 20m Maximum |
| **Operating Temperature** | |
| Wireless Fingerprint Keypad | -20 °C~+60 °C (-4 °F~+140 °F) |
| Wireless Lock | -20 °C~+60 °C (-4 °F~+140 °F) |
| **Operating Humidity** | 0%~86%RH |
| **Physical** | |
| Wireless Lock,Wireless Fingerprint Keypad | Zinc-Alloy |
| Others | ABS Shell |
| **Dimensions** | |
| Wireless Fingerprint Keypad | L149 x W43.5 x D22(mm) |
| Wireless Lock | L170 x W39 x D25(mm) |
| Wireless Exit Button | L83 x W40 x D16(mm) |
| Remote Transmitter | L62 x W30 x D11.5(mm) |

