
dimax

SWITCH DE 8 PUERTOS GIGABIT RJ45

Z049



CARACTERÍSTICAS

- 8 puertos Gigabit RJ45
- Compatible con los estándares IEEE 802.3, IEEE 802.3u e IEEE 802.3ab
- Los puertos Ethernet admiten velocidades adaptativas de 10/100/1000 Mbps
- Compatible con Auto MDI/MDIX
- Indicadores en el panel para monitorizar el estado de funcionamiento y facilitar el análisis de fallos
- Control de flujo: dúplex completo según el estándar IEEE 802.3x, semidúplex según el estándar de contrapresión

DESCRIPCIÓN

El switch Ethernet inteligente Gigabit de 8 puertos incorpora circuitos integrados de red de alta calidad y velocidad. Este producto, gracias a su diseño silencioso sin ventilador, resuelve por completo el problema del ruido que suelen generar los switches pequeños en entornos de oficina.

Este switch cuenta con 5 puertos Gigabit RJ45, que proporcionan una conexión fluida para Ethernet 10/100/1000M, facilitando su gestión y mantenimiento.

Es ideal para su uso en sistemas de videovigilancia de seguridad, hoteles, campus universitarios, ingeniería de redes en pequeñas y medianas empresas, entre otras aplicaciones.

ESPECIFICACIONES

I/O Interface	
Power	DC 5V
Ethernet	8*Gigabit RJ45 Ports
Chip Solution	
Main Chip	EN8851F
Performance	
Switching Capacity	16Gbps
Throughput	11.90Mpps
MAC Address	2K
Jumbo Frame	15Kbytes
Transfer Mode	Store and forward
MTBF	100000 Hours
Network Parameters	
Network Protocol	IEEE802.3 (10Base-T) IEEE802.3u (100Base-TX) IEEE802.3ab (1000Base-TX) IEEE802.3x (Flow control)
Network Medium	10Base-T : Cat3,4,5 or above UTP(≤100m) 100Base-TX : Cat5 or above UTP(≤100m) 1000Base-TX : Cat5 or above UTP(≤100m)
Certification	
Safety certificate	CE、FCC、RoHS
Environmental Standards	
Working Environment	Working Temperature: -10~50℃ Storage Temperature: -20~70℃ Working Humidity : 10%~90%, non-condensing Storage Temperature: 5%~90%, non-condensing
Indication	
LED Indicators	PWR(Power indicator)、Link(Network Link)
PWR	On: power on Off: no power
Link	On: 10/100/1000M link connection is normal Blinking: Data transmission is normal Off: link failure
Mechanical	
Structure Size	Product Size: 146*60*21.5mm Packing Size: 150*88*58mm Product Weight: 0.111Kg Packing Weight: 0.221Kg
Packing Info	Outer box size: 460*368*320mm Packing quantity: 60PCS Packing weight: 14.26KG
Operating Voltage	Power interface: DC2.1 Switch input voltage: DC 5V1A
Total power	5W
Packing list	1. Switch:1 PCS 2. User manual :1PCS 3. Warranty :1 PCS 4. Power Adapter:1 PCS