VIDEOPORTERO DE ACCESO CON TECLADO

R314

CARACTERÍSTICAS

- Resistente al agua, conforme a IP65
- Carcasa de metal, antivandálica
- Tipo de tarjeta: Tarjeta EM
- Disponible para iOS y Android
- Agregar/Eliminar usuarios mediante la aplicación
- Puede establecer restricciones de tiempo para los usuarios
- Admite verificación de operaciones





ESPECIFICACIONES

User Capacity Common User Visitor User	**Hardware User: 1000 APP User: 500** 990 (PIN/Card Users) 10
PIN Length	**4~6 digits**
Operating Voltage Idle Current Active Current	**12~18V DC** ≤ 60mA ≤ 150mA
Proximity Card Reader Radio Technlogy Read Range	**EM** 125KHz 2~6cm
Wiring Connections	**Relay output, exit button, Wiegand input/output**
Relay Adjustable Relay Output Time Lock Output Load	**One (NO, NC, Common)** 0~99 Seconds (5 seconds default) 2 Amp Maximum
Wiegand Interface PIN Output	**Wiegand 26~44 bits input & output** (Factory default: Wiegand 26bits) 4 bits,8bits (ASCII),10 digits Virtual Number(Factory default:4bits)
Environment Operating Temperature Operating Humidity	**Meets IP65** -40°C ~ 60°C (-40°F ~ 140°F) 0%RH ~ 92%RH
Physical Color Dimensions Unit Weight Shipping Weight	**Zinc-Alloy** Sliver & Black L142 x W48 x H22 (mm) 315g 410g