

Bullet 3 Pro

3MP/5MP

H.265 Outdoor Wi-Fi Camera

Bullet 3 Pro delivers 3MP/5MP live monitoring with a choice of 2.8mm/3.6mm F1.6 lens option, it supports four night vision modes for clear-as day clarity even in pitch dark. With IP67 certified, the camera can be used outdoors under different weather conditions. With built-in spotlight， Support Red & Blue alarm lightsand and 110dB security siren, Bullet 3 Pro actively keeps unwelcome visitors away from what you care about. Bullet 3 Pro support Human & vehicle Detection,quickly finds human & vehicle targets in images and immediately sends a notification to you.

3MP/5MP Video
High clarity of 2K/3K Ultra HD

Red-Blue Warning Lights
Provide a stronger deterrent

Human & Vehicle Detection
Quickly find human & vehicle targets in you home

Two-way Talk
Real-time communicate with people at the camera

Smart Full-Color Night Vision
Automatically turn into color mode From infrared mode

Diversified Storage
Supports NVR, Cloud Storage or Micro SD card(up to 512GB)

AOR Mode
Always-On-Record mode saves more storage space

IP67
Weatherproof from dust and water

2.4G Wi-Fi 6
IEEE802.11b/g/n/a/ax (2.4GHz WIFI 6)



Stay close with what you care

With Cloud service,you will have access to what you care as long as Internet is available.You can record daily or motion videos on Cloud and play back anytime anywhere.

Front View



Bottom View



Specifications

Camera

Image Sensor	1/2.9”Progressive CMOS
Max Resolution	3MP(2304*1296) 5MP(2880×1620)
Night Vision	25m Distance
Focal Length	3MP: 2.8mm V:111°,D:96°,H:52°; 3.6mm V:91°,D:78°,H:41°; 5MP: 2.8mm V:111°,D:94°,H:52°; 3.6mm V:91°,D:76°,H:41°;

Auxiliary Interface

Micro SD Card	up to 512GB
Built in Mic & Speaker	Yes
Reset Button	Yes

Notice Management

Human Detection	YES
Vehicle Detection	YES
Motion Detection	YES
Configurable Region	YES

Network

Wi-Fi	2.4GHz Wi-Fi 6 （IEEE802.11b/g/n/ax）
Ethernet port	1 x 100Mbps Ethernet Port
Imou App	iOS, Android
Onvif	Yes

Video & Audio

Video Compression	H.265/H.264
Video Frame Rate	20fps Frame rate
Focal Length	8×Digital Zoom
Sound Channel	Two-way Audio

General

Power supply	DC 12V 1A
Power Consumption	＜9W
Working Environment	-30℃~+50℃, Less Than 95%RH
Dimension(L×W×H) Weight	147.7 × 74.2 × 75.6mm 0.290kg

What’s in the box

Camera×1	Screw Package×1	Quick Start Guide×1	Mounting Plate×1
Power Adapter×1	Installation Position Map×1		