DS-KAS-7M01
Accessory Kit



Items included: power supply × 1, exit button × 1, magnetic lock × 1, and lock bracket × 1

Power supply

- Input: 110 to 230 VAC
- Output: 12 VDC, 24 W
- Momentary current: 5 A
- Persistent current: 5 A
- Support backup battery charging and discharging

Button

- Stainless steel panel
- LED indicator

Magnetic lock

- Lock dimension: L * W * H: 250 mm * 28 mm * 48 mm (9.8" * 1.1" * 1.9")
- Holding force: Max. 272 kg (600 Lbs)

Lock bracket

- Suitable for magnetic lock
- L bracket dimensions: L * W * H: 250 mm * 46 mm *30 mm (9.8" * 1.8" *1.2")
- Z bracket dimensions: L * W * H: 180 mm * 47 mm * 47 mm (7.1" * 1.9" * 1.9")

▪ Specification

Power Supply	
Power supply	Power input: 110 to 230 VAC Power output: 12 VDC, 24 W
Model	DS-K7M-AW24
Power consumption	Power output: 24 W Momentary current: 5 A Persistent current: 2 A
Working temperature	-10 °C to 50 °C (14 °F to 122 °F)
Working humidity	< 95%
Dimensions	168 mm × 216 mm × 73.3 mm
Magnetic Lock	
Model	DS-K4H255S
Maximum holding force	Max. 272 kg (600 Lbs)
Power supply	12 VDC, 470 mA - 24 VDC, 235 mA
Working temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working humidity	0 to 90% (Relative humidity)
Dimensions	Lock Body: L×W×H: 250 mm × 28 mm × 48 mm (9.8" × 1.1" × 1.9") Armature Plate: L×W×H: 180 mm × 38 mm × 12 mm (7.1" × 1.5" × 0.5")
Door type	Wooden door, glass door, and metal Door
Shell performance	Hard Anodizing electroplating operated
Lock body	Eco-friendly Zinc electroplating operated
Armature plate	Eco-friendly Zinc electroplating operated
Bracket of Magnetic Lock	
Model	DS-K4H255-LZ
Dimensions	L-bracket Dimension (L×W×H): 250×46×30mm (9.8×1.8×1.2"); Z-bracket Dimension (L×W×H): 180×47×47mm (7.1×1.9×1.9")
Suitable Door	Wooden door, glass door, and metal door
Shell performance	High strength aluminum alloy surface sandblasting oxidation
Exit Button	
Model	DS-K7P07
Power supply	12 to 24 VDC
Working temperature	-20 °C to 55 °C (-4 °F to 131 °F)
Working humidity	0 to 95% (Relative humidity)
Dimensions	115 mm × 70 mm × 16 mm (4.53" × 2.76" × 0.63")
Material	Panel: stainless steel

▪ Available Model

DS-KAS-7M01

Headquarters
No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com

Follow us on social media to get the latest product and solution information.

Hikvision HikvisionHQ HikvisionHQ Hikvision_Global Hikvision Corporate Channel hikvisionhq

©Hikvision Digital Technology Co., Ltd. 2023 I Data subject to change without notice I