DS-K1802
Value 1802 Card Reader (EM & MF & Keyboard)



- M1/ EM card reader
- PC+ABS material shell
- Built-in audible beeper
- Wiegand interface
- IP65

▪ Specification

Authentication	
Card reading frequency	13.56MHz/125KHz
General	
Power supply	12 VDC
Power consumption	≤ 1.6 W
Working temperature	-20 °C to 65 °C (-4 °F to 149 °F)
Working humidity	10% to 90% (no condensing)
Dimensions	115.9 mm × 43.3 mm × 17 mm (4.56"×1.70"×0.67")
Installation	Wall mounting with screws; Do not support gang box
Weight	Gross weight: 0.217 kg (0.48 lb) Net weight: 0.12 kg (0.26 lb)
Keypad	DS-K1802E/DS-K1802M: No keypad DS-K1802EK/DS-K1802MK: Keypad with 12 keys (0 to 9, *, #)
Buzzer	Support

▪ Available Model

DS-K1802E

▪ Accessory

▪Optional

DS-K2801 Value Series Card Access Contoller	ACT-C101#RUBB Value Series Card Access Contoller
	

Headquarters
No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com

Follow us on social media to get the latest product and solution information.

Hikvision HikvisionHQ HikvisionHQ Hikvision_Global Hikvision Corporate Channel hikvisionhq

©Hikvision Digital Technology Co., Ltd. 2023 I Data subject to change without notice I