DS-PK201B-WB
Wireless LED Keypad



- Simple and elegant appearance design
- Clear LED indication for the status of system, physical keys for faster operation
- One-Push FIRE, PANIC, and MEDICAL alarm
- Duress code used in emergency situation
- Frequency hopping against jamming for reliable transmission

▪ Specification

Communication	
Transmission technology	433.1-433.7 MHz
Transmission range (free space)	Up to 1,000 m
Maximum effective radiated power (ERP)	25 mW max
Radio signal modulation	2GFSK
Software features	
Temperature indicator	Yes
Indication	
Indication method	Buzzer and LED
Hardware features	
Tamper-Proof	Yes
Keypad type	Physical Keypad
Access	
User passcode	Yes
Protection against code guessing	Yes
Duress code	Yes
Electrical characteristics	
Power supply	4 × AA batteries
Power consumption	max current: 190 mA quiescent current: 30 uA
Battery life	Up to 2 years (standby time)
General	
Operation temperature	-10 °C to 55 °C (14 °F to 131 °F)
Operation humidity	10% to 90%
Dimension(WxHxD)	96 x 96 x 26.3 mm
Weight	127 g

▪ Available Model

DS-PK201B-WB

Headquarters
No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com

Follow us on social media to get the latest product and solution information.

Hikvision HikvisionHQ HikvisionHQ Hikvision_Global Hikvision Corporate Channel hikvisionhq

© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.